

Tender Sample Text

ROKO

| R | 0 | K | 0 | ga | bid | on | ba | asl | cet | ts |
|---|---|---|---|----|-----|----|----|-----|-----|----|
|---|---|---|---|----|-----|----|----|-----|-----|----|

To provide and install wire mesh baskets with a filling of hard and durable, sufficiently strong frost, weather and pressure resistant stone material.

Wire mesh baskets, made of electro-spot-welded, steel-wire mesh-grids with

| a tensile stren | gth of ≥ 450 N | /mm². | 3 | | | | | |
|-------------------------------------|--|---------------------------------------|----------------------|--|--|--|--|--|
| basket sizes (s | tandard): | Length: 50cm/100cm/150cm/200cm | | | | | | |
| | | Width: 50cm/100cm | | | | | | |
| | | Height: 50cm/100 | lcm | | | | | |
| <u>basket size:</u> | | (LxWxH in cm) _ | | cm | | | | |
| mesh size: | | 5x10cm/10x10cm | | | | | | |
| wire size: | | Ø 4,5mm/5,0mm | | | | | | |
| helical rod: | | wire-Ø 4,5mm | | | | | | |
| staying rod: | | wire-Ø 5,0mm | | | | | | |
| | IN EN ISO 922 trength of mir | 7:2006-10 NSS, with m n.450 N/mm². | | e of min. 3.000 h salt spray testing, s as a minimum thickness of 350g/m² | | | | |
| Connection of | grids optiona | lly with helical rods or | c-clips | | | | | |
| To install compose of supplier at o | · · | | naterials without vo | oids according assembly instructions | | | | |
| Filling: | Sufficiently hard, durable, strong frost, weather and pressure resistant stone material. The grain size has to be bigger than the mesh size. | | | | | | | |
| Total Height: | up to | | m | | | | | |
| | consisting o | f | pieces (Lx\ | WxH)/baskets | | | | |



Proof of delivery: Rothfuss Best Gabion GmbH & Co. KG

Dr.-Oetker-Straße 30

54516 Wittlich kontakt@rbg.eu Tel.: 06571/95233-0

Fax: 06571/95233-55

or similar